



FWX6250

cod. FWX-6250


MUSCOLI COINVOLTI
MUSCLE GROUPS

- Pettorali - Pectorals
- Tricipiti - Triceps
- Deltoide anteriore - Anterior deltoid



SISTEMA DI SPINTA a leveraggio singolo
 DIMENSIONI PRODOTTO: 1200x1430x1700 mm
 PESO MAX UTILIZZATORE 160 Kg
 PESO MAX CARICABILE 300 Kg
 PESO: 230 Kg
 CLASSE D'UTILIZZO PROFESSIONALE (EN20957-1 / EN957-2 CLASSE S)

SINGLE PUSH leverage system
 SET UP SIZE: 1200x1430x1700 mm
 MAX USER WEIGHT 160 Kg
 MAX LOADABLE WEIGHT 300 Kg
 WEIGHT: 230 Kg
 COMMERCIAL USE (EN20957-1 / EN957-2 CLASS S)

- Struttura tubolare in acciaio a sezione quadrata 75x75 e rettangolare 50x80 mm - spessore 3 mm
- Verniciatura doppia a polveri epossidiche, antigraffio. Trattamento dei tubolari con sabbiatura e fosfatazione
- Sistema di cuscinetti POWER GRADE per garantire uno scorrimento preciso e progressivo
- Cuscini in schiuma ad alta densità con rivestimento in PU
- Structure squared and rectangular heavy-duty steel tubing 75x75 and 50x80 mm - thickness 3 mm
- Double heavy duty powder coating painting, scratch-resistant. Tubing treatment with sandblastic and phosphating process
- Pulleys system POWER GRADE bearings for a smooth and precise action
- High-density foam cushions with PU upholstery

